

		Model	Cutting Width	Hydraulic Flow	Max Cut	Motor Type	Drive Type	Motor Protection	Tip Speed	Max PSI Rating	Blade Carrier Type	Blades	Deck Thickness	Chain Cur-tain(s)	Weight
CLOSED FRONT	COMPACT	4800 LF	48 in	8-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	7,500-14,000 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Front; rear	672 lbs
		4800 SF	48 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,750-18,400 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Front; rear	690 lbs
	HEAVY-DUTY	6000 LF	60 in	10-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	9,300-14,000 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 22 X 4 X 0.5 in; updraft	1/4 in	Front; rear	950 lbs
		6000 SF	60 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,500-18,000 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 22 X 4 X 0.5 in; updraft	1/4 in	Front; rear	950 lbs
		6600 LF	66 in	10-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	8,000-12,000 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 25 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,050 lbs
		6600 SF	66 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,200-17,500 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 25 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,050 lbs
		7200 LF	72 in	15-20 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	13,000-17,400 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,160 lbs
		7200 SF	72 in	21-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	13,800-17,400 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,160 lbs
		7200 HF	72 in	26-40 GPM	5 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,500-17,600 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,160 lbs
		7800 SF	78 in	20-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	15,000-17,800 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 31 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,280 lbs
		7800 HF	78 in	26-40 GPM	5 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	12,500-19,200 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 31 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,340 lbs
		9000 SF	90 in	20-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	14,200-17,800 ft/min	3,000/3,500	(2) 1" GRD-50 discs	(4) 14.75 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,790 lbs
	9000 HF	90 in	26-40 GPM	5 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	9,600-14,800 ft/min	3,000/3,500	(2) 1" GRD-50 discs	(4) 14.75 x 4 x 0.5 in; updraft	1/4 in	Front; rear	1,840 lbs	
OPEN FRONT	COMPACT	4801 LF	48 in	8-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	7,500-14,000 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Rear	672 lbs
		4801 SF	48 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,750-18,400 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Rear	690 lbs
	STANDARD-DUTY	SD6000 LF	60 in	10-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	9,300-14,000 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 22 X 4 X 0.5 in; non-updraft	1/4 in	—	840 lbs
		SD6000 SF	60 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,500-18,000 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 22 X 4 X 0.5 in; non-updraft	1/4 in	—	840 lbs
		SD7200 LF	72 in	15-20 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	13,000-17,400 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 X 4 X 0.5 in; non-updraft	1/4 in	—	1,000 lbs
		SD7200 SF	72 in	21-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	13,800-17,400 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 X 4 X 0.5 in; non-updraft	1/4 in	—	1,000 lbs
		6601 LF	66 in	10-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	8,000-12,000 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 25 x 4 x 0.5 in; updraft	1/4 in	Rear	1,224 lbs
	HEAVY-DUTY	6601 SF	66 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,200-17,500 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 25 x 4 x 0.5 in; updraft	1/4 in	Rear	1,224 lbs
		7201 LF	72 in	15-20 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	13,000-17,400 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 x 4 0.5 in; non-updraft	1/4 in	Rear	1,220 lbs
		7201 SF	72 in	21-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	13,800-17,400 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 x 4 0.5 in; non-updraft	1/4 in	Rear	1,220 lbs
		7201 HF	72 in	26-40 GPM	5 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,500-17,600 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 28 x 4 0.5 in; non-updraft	1/4 in	Rear	1,220 lbs
		7801 SF	78 in	20-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	15,000-17,800 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 31 x 4 x 0.5 in; updraft	1/4 in	Rear	1,310 lbs
		7801 HF	78 in	26-40 GPM	5 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	12,500-19,200 ft/min	3,000/3,500	5/16" spun-formed pan	(2) 31 x 4 x 0.5 in; updraft	1/4 in	Rear	1,386 lbs
		72 HD/O	72 in	23-29 GPM	8 in	Radial piston hydraulic	Direct drive	Pressure relief valves, case drain	10,300-13,000 ft/min	4,000	1" GRD-50 disc	(3) 25 x 4 x 0.5 in; non-updraft	1/4 in	—	1,494 lbs
		72 XP/O	72 in	30-40 GPM	8 in	Radial piston hydraulic	Direct drive	Pressure relief valves, case drain	13,000-16,000 ft/min	4,000	1" GRD-50 disc	(3) 25 x 4 x 0.5 in; non-updraft	1/4 in	—	1,494 lbs
	EXTREME-DUTY	78 HD/O	78 in	23-29 GPM	8 in	Radial piston hydraulic	Direct drive	Pressure relief valves, case drain	11,100-14,000 ft/min	4,000	1" GRD-50 disc	(3) 28 x 4 x 0.5 in; non-updraft	1/4 in	—	1,610 lbs
78 XP/O		78 in	30-40 GPM	8 in	Radial piston hydraulic	Direct drive	Pressure relief valves, case drain	13,000-17,300 ft/min	4,000	1" GRD-50 disc	(3) 28 x 4 x 0.5 in; non-updraft	1/4 in	—	1,610 lbs	
ALPHA HD		72 in	30-40 GPM	10 in	Radial piston hydraulic	Direct drive	Pressure relief valves, case drain	10,300-14,300 ft/min	3,000/4,100	1" GRD-50 disc OR two-piece 5/8" steel discs	(3) 18 x 5 x 0.625 in; non-updraft drop-blades OR	1/4 in	—	2,320/2,570 lbs	
ALPHA XP		72 in	33-45 GPM	10 in	Radial piston hydraulic	Direct drive	Pressure relief valves, case drain	13,200-18,000 ft/min	3,000/4,100		(4) 18 x 8.5 x 0.625 in; Hardox® 500 non-updraft flat-blades	1/4 in	—	2,320/2,570 lbs	